

cleanslate

Previously Twenty Five



Claremont Chlorinated Caustic Cleaner

High Foaming

Claremont is a heavy duty, foaming, chlorinated liquid alkaline cleaner. Claremont contains a blend of biodegradable synthetic detergents, foam stabilizers, alkaline builders, water softeners, and chlorine. For use on all types of non-porous metal surfaces, including aluminum and galvanized.

DIRECTIONS FOR USE

FOR FOAM CLEANING: Mix 2 to 5 ounces per gallon of hot water. Apply as a foam to all surfaces. Allow contact time of 5 to 10 minutes and scrub thoroughly with brush. Do not allow solution to dry. Rinse all surfaces thoroughly. **FOR MEDIUM-DUTY STEAM CLEANING:** Dilute 2 to 6 ounces per gallon of water and apply with a steam cleaner. Rinse thoroughly with water. **FOR HIGH PRESSURE WASHING:** Dilute 2 to 4 ounces per gallon of water and apply with pressure sprayer. Rinse surfaces thoroughly with water.

DANGER HAZARD STATEMENTS

Causes severe skin burns and eye damage. May be corrosive to metals.

PRECAUTIONARY STATEMENTS

Wear protective gloves, splash goggles, face shield, full suit, vapor respirator and boots. Do not breathe mist /vapors /spray. Wash thoroughly after handling.

FIRST AID

Eye Contact. Check for and remove any contact lenses. Flush with large quantities of water, holding eyelids open for 15 minutes. Seek medical attention immediately. **Skin Contact.** Wash skin with copious amount of water. Seek medical attention immediately. **Inhalation.** Remove to fresh air. Seek medical attention immediately. **Ingestion.** Do not induce vomiting. Drink copious amounts of water. Seek medical attention immediately.



STORAGE

Store in original container protected from sunlight, well ventilated area, away from incompatible materials, food and drink. Keep out of reach of children.

SPILL/LEAK

Avoid runoff into storm sewers and ditches which leads to waterways. Absorb spillage with an inert dry material and place in an appropriate waste disposal container.

DISPOSAL

Dispose of material in accordance with local, state and federal regulations.

HAZARDOUS INGREDIENTS

Potassium Hydroxide (1310-58-3)
Sodium Hydroxide (1310-73-2)
Sodium Hypochlorite (7681-52-9)
Sodium Xylene Sulfonate (1300-72-7)
Lauramine Oxide (1643-20-5)

OUR PROMISE

**SAFER &
STRONGER™**



Biodegradable
Surfactants



Commercial
Grade



Phosphorous
Free



Fast
Acting

SCAN FOR SDS



Item #4027



Toll-Free 866.510.8080
Emergency 800.424.9300
cleanslategrp.com
info@cleanslategrp.com
1420 E Linden Ave, Linden, NJ 07036

